

HOLDER ON & RIVETING HAMMER



HOLDER ON (DOLLY MACHINE)

BULLSCAT Holders-On are built to buck up rivets against the hardest blow of the hammer, insuring a strongly riveted joint and a completely filled rivet hole. Rivet heads are not mutilated, as there is no inclination to jump. Another advantage of using these holders-on is the fact that they speed up the riveting operation.

FEATURES:

Alloy steel harden cylinder & piston provide excellent durability. Bucket with piston o ring gives extra support during riveting.



Holder On (Dolly Machine) CAT 600



Riveting Hammer CAT 3007

Model No.	Rivet holding capacity in mm	Feeding length mm	Length retracted mm	Total length extracted mm	OPERATING Pressure PSI	APPROX. Weight Kg.	AIR Inlet	MIN. Hose size
CAT 600	16-25	130	132	232	90	6.5	1/2"	1/2"
CAT 400	16-25	100	100	175	90	4.9	1/2"	1/2"

RIVETING HAMMER

BULLSCAT offers one of the most comprehensive range of Riveting Hammer. They are powerful & versatile most suited for riveting

FEATURES .

- Rugged construction harened steel piston, cylinder & handle.
- Teasing throttle for precise control.

Model No.	Riveting capacity in steel (Hot) mm	Blows per minute bpm	Handle type	Length in mm	OPERATING Pressure PSI	APPROX. Weight Kg.	AIR Inlet	MIN. Hose size	Standard Equipment
CAT 3005	20	1500	Pistol Grip	430	90	9.2	1/2"	3/4"	Snap Clip reatiner
CAT 3006	24	1320	Pistol Grip	470	90	10.0	1/2"	3/4"	Snap Clip reatiner
CAT 3007	30	1200	Pistol Grip	523	90	10.8	1/2"	3/4"	Snap Clip reatiner
CAT 3010	27	720	Pistol Grip	660	90	15.0	1/2"	3/4"	Chisel retainer & Rubber Bumper

CONSTRUCTION AIR TOOLS